IN THE CLAIMS

- 1. (canceled)
- 2. (canceled)
- 3. (currently amended) The bracket assembly of claim 10, wherein the protective device mounting portion is a tab portion of the bracket assembly.
- 4. (currently amended) The bracket assembly of claim 10, wherein the bracket <u>assembly</u> further comprises a bulkhead mounting portion operable to attach to a bulkhead surface and wherein the protective device mounting portion is not in contact with the bulkhead mounting portion of the bracket <u>assembly</u>.
- 5. (currently amended) The bracket assembly of claim 10, wherein the protective device mounting portion of the bracket <u>assembly</u> further comprises a protective device mounting element that in cooperation with the protective device retaining <u>portion</u> <u>element</u> couples the protective device to the bracket <u>assembly</u>.
- 6. (currently amended) The bracket assembly of claim 10, wherein the protective device further comprises first and second protective devices, the protective device mounting portion further comprises first and second tab portions of the bracket assembly, and wherein the protective device retaining element further comprises a first protective device retaining portion operable to couple the first protective device to the first tab portion and a second protective device retaining portion operable to couple the second protective device to the second tab portion.
- 7. (currently amended) The bracket assembly of claim 10, wherein the protective device comprises a plurality of protective devices.
- 8. (canceled)

bulkhead with the exception of a portion of the power connector remaining externa
to the bulkhead.
10. (currently amended) <u>A power cabling assembly, comprising:</u>
a bracket assembly having at least one electrical protective device integra
thereto;
a power connector; and
a bracket power connector fastening element operable to couple the power
connector to a bulkhead and the bulkhead to the bracket assembly,
wherein the bracket assembly further comprises a protective device mounting
portion to which the protective device is coupled by a protective device retaining
element and The power cabling assembly of claim 8, wherein the power cabling
assembly further comprises first and second cables coupled to the power connector
and a plurality of cables coupled to the protective device.
11. (currently amended) <u>A power cabling assembly, comprising:</u>
a bracket assembly having at least one electrical protective device integra
thereto;
a power connector; and
a bracket power connector fastening element operable to couple the power
connector to a bulkhead and the bulkhead to the bracket assembly,
wherein the bracket assembly further comprises a protective device mounting
portion to which the protective device is coupled by a protective device retaining
element and The power cabling assembly of claim 8, wherein the power cabling
assembly further comprises first and second cables coupled to the protective device
12. (currently amended) The power cabling assembly of claim [[8]]10, wherein the

wherein said assembly may be inserted through a receiving portion of [[a]]the

The power cabling assembly of claim [[8]]10,

power cabling assembly further comprises first and second output connectors

coupled to a plurality of cables of said assembly.

9.

(currently amended)

13. (canceled)

14. (currently amended) The bracket assembly of claim [[8]]11, wherein the

protective device mounting portion is a tab portion of the bracket assembly.

15. (currently amended) The bracket assembly of claim [[8]]11, wherein the

bracket assembly further comprises a bulkhead mounting portion operable to attach

to a bulkhead surface and wherein the protective device mounting portion is not in

contact with the bulkhead mounting portion of the bracket assembly.

16. (currently amended) The bracket assembly of claim [[8]]11, wherein the

protective device mounting portion of the bracket assembly further comprises a

protective device mounting portionelement that in cooperation with the protective

device retaining deviceelement couples the protective device to the bracket

assembly.

17. (currently amended) The bracket assembly of claim [[8]]11, wherein the

protective device further comprises first and second protective devices, the

protective device mounting portion further comprises first and second tab portions of

the bracket assembly, and wherein the protective device retaining deviceelement

further comprises a first protective device retaining deviceportion operable to couple

the first protective device to the first tab portion and a second protective device

retaining deviceportion operable to couple the second protective device to the

second tab portion.

18. (currently amended) A power cabling assembly, comprising:

a bracket assembly having at least one electrical protective device integral

thereto;

a power connector; and

a bracket power connector fastening element operable to couple the power

connector to a bulkhead and the bulkhead to the bracket assembly,

wherein the bracket assembly further comprises a protective device mounting portion to which the protective device is coupled by a protective device retaining element The power cabling assembly of claim 8,

wherein said assembly may be inserted through a receiving portion of a bulkhead, with first and second cables of a plurality of cables of said assembly coupled to the power connector, fourth third and fourth cables of the plurality of cables coupled to the protective device element, first and second output connectors coupled to the plurality of cables, and a protective device mounting portion to which the protective device is coupled by the means for coupling, wherein the protective device mounting portion is a tab portion of the bracket assembly, wherein the bracket assembly further comprises a bulkhead mounting portion operable to attach to a bulkhead surface, and wherein the protective device mounting portion is not in contact with the bulkhead mounting portion of the bracket assembly.

- 19. (canceled)
- 20. (canceled)
- 21. (canceled)
- 22. (canceled)
- 23. (canceled)
- 24. (canceled)
- 25. (new) The bracket assembly of claim 11, wherein the protective device comprises a plurality of protective devices.

26. (new) The power cabling assembly of claim 11, wherein said assembly may

be inserted through a receiving portion of the bulkhead with the exception of a

portion of the power connector remaining external to the bulkhead.

27. (new) The power cabling assembly of claim 11, wherein the power cabling

assembly further comprises first and second output connectors coupled to a plurality

of cables of said assembly.

28. (new) The bracket assembly of claim 18, wherein the protective device

mounting portion is a tab portion of the bracket assembly.

29. (new) The bracket assembly of claim 18, wherein the bracket assembly

further comprises a bulkhead mounting portion operable to attach to a bulkhead

surface and wherein the protective device mounting portion is not in contact with the

bulkhead mounting portion of the bracket assembly.

30. (new) The bracket assembly of claim 18, wherein the protective device

mounting portion of the bracket assembly further comprises a protective device

mounting element that in cooperation with the protective device retaining element

couples the protective device to the bracket assembly.

31. (new) The bracket assembly of claim 18, wherein the protective device

further comprises first and second protective devices, the protective device

mounting portion further comprises first and second tab portions of the bracket

assembly, and wherein the protective device retaining element further comprises a

first protective device retaining portion operable to couple the first protective device

to the first tab portion and a second protective device retaining portion operable to

couple the second protective device to the second tab portion.

32. (new) The bracket assembly of claim 18, wherein the protective device

comprises a plurality of protective devices.

6

- 33. (new) The power cabling assembly of claim 18, wherein said assembly may be inserted through a receiving portion of the bulkhead with the exception of a portion of the power connector remaining external to the bulkhead.
- 34. (new) The power cabling assembly of claim 18, wherein the power cabling assembly further comprises first and second output connectors coupled to a plurality of cables of said assembly.